



PRODUCT INFORMATION SHEET

Product Name: AUTOMAX SYNTEC

Date Issued: 23rd October 2008

PRODUCT

Prolube Automax Syntec is an Automatic Transmission Fluid formulated from Synthetic base oils blended with a new generation additive package to provide a highly shear-stable automatic transmission fluid which meets the specific requirements of the GM Dexron IIIH and Ford Mercon® -V.

It extends transmission life via performance anti-wear additives, enhanced frictional properties for smoother gear changes, reduced deposit formations due to superior oxidation inhibitors, reduced foaming, longer service life due to the full synthetic base stocks and shear-stable additive technology.

APPLICATION

Recommended for automatic transmissions in Holden Commodore and Toyota Lexcen, Mitsubishi, Honda where ATF '89 is specified (to 1996).

STANDARDS

Meets the performance requirements of:

- General Motors Dexron® III G/H
- Ford MERCON ®
- MAN 339F
- Volvo 97340
- Ford MERCON-V®
- Allison C4
- Voith 55.6335.32 (G607)
- ZF TE-ML 16L / 17C

Recommended for use for the following applications:

- Chrysler ATF+3®, +4®
- Honda Z-1
- BMW LA2634, LT71141
- Mercedes Benz 236.x
- Allison TES-295
- Hyundai/Kia SP-II, SP-III
- Voith H55.6336.33 (G1363)
- Chrysler ATF+, +2, +2 Type 7176
- Nissanmatic D, J, K
- Toyota T-IV, T-III, T
- GM Dexron®, Dexron® II, IID
- Mitsubishi Diamond SP-II, III
- VW TL52162
- ZF TE-ML 14B

Not recommended for Type F / Volvo 5 Speed / MERCON SP / Dexron VI / Toyota WS / Mercedes Benz NAG-2 / CVT Applications

CONTAINER SIZES

205 Litres,

60 Litres,

20 Litres,

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,

35 Kremzow Road,

Brendale, Qld. 4500.

Telephone: (07) 3881 1733

Fax: (07) 3881 1708

Email: admin@prolube.com.au

Internet: www.prolube.com.au