



PRODUCT INFORMATION SHEET

Product Name: HVX.MS 15W50 SL CF

Date Issued: 19th March, 2007

PRODUCT

Prolube HVX.MS engine oil has modern technology for late model, high stress applications. It provides the maximum protection against wear, corrosion, oxidation and sludge formation and is particularly suitable for naturally-aspirated and turbo-charged models. HVX.MS oil can be used in light and medium duty diesel engines and it provides enhanced valve train lubrication in modern unleaded petrol and LP gas motors as well as four stroke motorcycles fitted with wet clutches.

APPLICATION

This oil is designed for all 4 stroke and rotary petrol motors using LP, ULP, PULP and LP gas fuels and requiring an SAE 15W50 engine oil. Although it was specifically designed for post-1997 model motors, including multi-valve and turbo-charged motors, it is also suitable for light duty passenger car style diesel motors.

STANDARDS

Meets or exceeds the following:

SAE Grade: 15W50
API: SL CF
ACEA: A2/B3

CONTAINER SIZES

205 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
35 Kremzow Road,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au