



## PRODUCT INFORMATION SHEET

**Product Name:** HVX.TURBO 15W50 CH-4 SJ

**Date Issued:** 19<sup>th</sup> March, 2007

### PRODUCT

Prolube HVX.Turbo 15W50 combines the very latest additive technology and high quality base oils to provide a lubricant with exceptional performance in the latest model turbo-charged diesel and petrol engines. This product ensures less oil thickening, better oxidation and corrosion resistance, less wear and improved all-round performance. It is recommended for mixed fleet service where late model vehicles are in use, particularly where they work under hot or adverse conditions.

### APPLICATION

Designed for 4 stroke motors using LP, ULP, PULP, LPG and diesel fuels particularly in high performance applications. It is specifically designed as an alternative to synthetic lubricants and as a means of maintaining component protection in high stress applications.

### STANDARDS

Meets or exceeds the following:

SAE Grade: 15W50

API: CH-4 SJ

ACEA07-E2

ACEA04-E2

ACEA02(obsolete) – E2/B3/A2

Allison C-4

ZF TE-ML 07C

Mercedes Benz 228.3/229.1

Volvo VDS-2

Mack EO-M Plus

Cummins 20071,76

CAT ECF-1-a

MAN 271

MTU TYPE 1

Renault RD/RD-2

### CONTAINER SIZES

205 Litres,

20 Litres,

5 Litres.

### CONTACT

**PROLUBE Lubricants,**

P.O. Box 5435,  
35 Kremzow Road,  
Brendale, Qld. 4500.

Telephone: (07) 3881.1733  
Fax: (07) 3881.1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.prolube.com.au](http://www.prolube.com.au)