



PRODUCT INFORMATION SHEET

Product Name: MAXIFLEET 15W40 CG-4 SJ

Date Issued: 1st October, 2005

PRODUCT

Prolube Maxifleet 15W40 is very shear stable, provides excellent protection against wear, corrosion and oxidation and ensures a high degree of engine cleanliness. It is suitable for naturally aspirated and turbo-charged diesel and petrol engines including those running on unleaded petrol.

APPLICATION

Designed for 4 Stroke motors using LP, ULP, PULP, LPG and diesel fuels where a 15W40 engine oil is specified or indicated. It is specifically designed for pre-1997 North American-style diesel motors requiring a low ash engine oil. The primary recommendation is for mixed fleet operations.

STANDARDS

Meets or exceeds the following:

SAE Grade:	15W40	Cummins:	NTC.400
API:	CG-4 SJ	Mack:	EO-K/2, EO-M
ACEA:	E2/A2/B3	Allison:	C3
		Volvo	VDS
		Mercedes Benz	228.1

CONTAINER SIZES

Bulk 205 Litres, 60 Litres, 20 Litres, 5 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
35 Kremzow Road,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au