



PRODUCT INFORMATION SHEET

Product Name: Multitec 15W40 SL CF

Date Issued: 19th March, 2007

PRODUCT

Prolube Multitec 15W40 SLCF is a heavily fortified oil which uses the latest additive technology to provide significantly better performance in late model petrol engines. It is suitable for naturally aspirated and turbocharged motors as well as four stroke motorcycles fitted with wet clutches. It ensures better rust and corrosion protection, less oil oxidation and superior deposit control and wear protection. This product is particularly recommended where the manufacturer requires the use of a lighter multigrade oil or where vehicles encounter lower temperature operation, providing superior component protection at cold start-up.

APPLICATION

This oil is designed for late model 4-stroke petrol motors, particularly multi-valve, multi-cam models requiring a low viscosity oil for fuel economy, low emissions and high performance. It has been formulated for applications where 5W30 to 10W30 engine oils are specified.

STANDARDS

Meets or exceeds the following:

SAE Grade:	15W40
API:	SL CF
ILSAC:	GF-2

CONTAINER SIZES

205 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
35 Kremzow Road,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.prolube.com.au