



PRODUCT INFORMATION SHEET

Product Name: ULTRAFLEET 15W40 CI-4/SL

Date Issued: 19th February, 2009

PRODUCT

Prolube Ultrafleet 15W40 has been formulated using new generation high performance base oils and the most recent additive technology to meet the latest CI-4 performance requirements. Ultrafleet 15W40 provides optimum protection and control of corrosion, oil thickening due to soot build up, piston deposits, oxidation, sludge build up and high temperature stability.

APPLICATION

Ultrafleet is a high performance mixed fleet lubricant designed for use in the latest European, US and Japanese four stroke diesel engines, including the new breed highly turbocharged and emission control designed engines. Ultrafleet is our primary recommendation for electronically controlled engines, where high soot loading is experienced and for extended drain or severe service conditions. Extended drain intervals should be in compliance with the engine manufacturer guidelines and in conjunction with oil analysis checks.

STANDARDS

Meets or exceeds the following:

SAE Grade: 15W40

API CI-4/SL

ACEA02 - E5/E3/B4/B3/A3

ACEA07 - E7/B4/A3

ACEA04 - E7/B4/B3/A3

MB.228.3/MD.229.1

Renault RLD/RLD-2

ZF TE-ML 07C

Cummins:CES 20071/2/6/7/20078

Mack EO-M PLUS

Detroit 7SE 270 4 cycle

MAN 3275

Global DHD-1

Volvo VDS2/VDS-3

Caterpillar ECF-1-a, ECF-2.

CONTAINER SIZES

Bulk, 205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
35 Kremzow Road,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733

Fax: (07) 3881.1708

Email: admin@prolube.com.au

Internet: www.prolube.com.au