



PRODUCT INFORMATION SHEET

Product Name: PRO SUPER PLANT GREASE

Date Issued: 23rd June 2004

PRODUCT

Prolube Pro Super Plant Grease possesses superior lubrication characteristics. It is recommended for bearing lubrication under all operating conditions from normal to unusually severe load conditions. Pro Super Plant Grease, which has a smooth and tacky texture, is the prime recommendation for automotive, marine and industrial applications.

Pro Super Plant Grease is manufactured with Lithium complete base, thickener and selected synthetic and paraffinic base oils combined with rust, oxidation and corrosion inhibitors, tackiness adhesives and additional more effective Extreme Pressure additives to cater for the unusually high load service conditions.

APPLICATION

Multi-purpose grease for high and low temperature applications. It protects against wear on all moving parts and shock loading to unusually high load services. It prevents scuffing and further assists in wear prevention because Pro Super Plant Grease has excellent shear stability as well as the high load extreme pressure characteristics.

STANDARDS

Meets or exceeds the following:

NLGI:	2
Drop Point	260+

CONTAINER SIZES

20 kg, 2.5 kg, 450 g cartridges.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
35 Kremzow Road,
Brendale, Qld. 4500.

Telephone:	(07) 3881 1733
Fax :	(07) 3881 1708:
Email:	admin@prolube.com.au
Internet:	www.prolube.com.au